



TS9155

15" Desktop Series LCD Resistive Monitor Touchmonitor

- USB Interface
- Resistive Monitor technology on pure glass for the ultimate image quality
- High quality panel with brightness and contrast adjustment
- Activated with fingernails, gloves or stylus
- Durable and stable tilt base
- Mounting holes on the bottom base for tabletop security
- Ability to connect to optional USB hub
- FCC, CE, CCC, RoHS



TS9155

15" Desktop Series LCD Resistive Monitor Touchmonitor

Applications

- Point-of-sale (POS)
- Point of service
- Loyalty systems
- Countertop kiosk information systems (KIS)
- Internet access points
- Interactive advertising and display
- Guest check in and check out



SPECIFICATION

Series	DT	
Case/bezel color	Dark gray	
LCD Type	Active matrix TFT-LCD	
Display Size	15" (diagonal)	
Active Area	12.0" (304mm)×9.0" (228mm)	
Suggested Resolution	1024×768	
Support Colors	16.2M	
Brightness(Typ.)	Pure LCD Panel	
	With Resistive Monitor Glass Sensor	250cd/m ²
Response Time(Typ.)	5ms	225cd/m ²
	Viewing Angle (Typ. at CR > 10)	Horizontal(left/right)
	Vertical(up/down)	70°/60°
Contrast Ratio(Typ.)	500:1	
Video Input	Analog RGB	
Signal Input	H/V Separate Sync. (TTL)	
Video Signal Input Connector	Mini D-Sub 15-pin VGA	
Frequency (H/V)	30~80KHz / 60~75Hz	
Power Supply	Type: Adaptor in base Input (line) voltage: 100-240 VAC, 50-60 Hz	
Environment	Operating Temp.	0~50°C
	Operating Temp.	-20~60°C
	Operating Temp.	20%~80%
	Operating Temp.	10%~90%
LCD Back light Life(Typ.)	50,000 Hours	
Weight (N.W/G.W)	Approximately 4Kg /5Kg	
Power Consumption	30W Max.	
Mount options	Threaded-through mounting holes under base	
OSD Control	Brightness, Contrast Ratio, Auto-adjust, Phase, Clock, H/V Location, Languages, Function, Reset	
Touch screen Type	15" Resistive Monitor 3MM thickness of touch screen (Available Options: Thickness/Anti-glare/Tempered)	
Touch Response time	9ms	
Touch System Interface	USB	
Agency approvals	FCC, CE, CCC, RoHS	
Other features	Optional USB Hub with 4 ports output	
NOTE: The display SPEC. will change follow the relevant LCD panel brand and model		

Contact your dealer :